

VARIABLE SPEED, EQUIPPED WITH LIGHT SYSTEM, CHUCK SPEED DIGITAL DISPLAY, DEPTH'S DIGITAL DISPLAY.



Max drilling capacity on steel with pre-drilling hole(s235jr)

Ø 16 mm

Face milling cutter max

Ø 63 mm

End milling capacity

Ø 20 mm

Spindle taper

CM 3

Chuck sizes

1 - 16 mm B16

Variable spindle speed

I 30 - 1650 rpm $\pm 10\%$ | II 2° 40 - 2850 rpm $\pm 10\%$

Spindle stroke

50 mm

Spindle rotation

Dx - Sx

Quill

60 mm

Headstock travel

290 mm

Head tilt left and right

$\pm 90^\circ$

Distance between spindle nose and table

350 mm

Table dimensions

700 x 180 mm

Slot

12 mm

Longitudinal axis

175 mm

Cross axis

490 mm

Motor

230 V 50 | 60 Hz 1,1 kW

Net weight

120 kg

Packaging dimensions

760x720x920 h mm

Gross weight

147,00 kg

EAN Code

8012667343583

Included

Drill chuck with key 1 - 16 mm B16
Drill chuck shank with hole MT 3
Oilcan
Draw bar M12
Service wrenches