

REVERSIBLE, WITH AUTOMATIC FEEDING, COOLANT SYSTEM,
REVERSIBLE TABLE WITH 145MM VICE INCLUDED, EQUIPPED WITH
LIGHT.



FERVIplus



Max drilling capacity on cast iron with pre-drilling hole	Ø 40 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 35 mm
Continuous drilling capacity	Ø 30mm
Spindle taper	MT 4
Chuck sizes	1 - 13 mm B16
Spindle speed	(12) 75 - 3200 rpm
Spindle travel	125 mm
Spindle rotation	Dx - Sx
Quill	Ø 75 mm
Column	Ø 125 mm
Feed range	(3) 0,1 - 0,18 - 0,26 mm/rev
Distance between spindle axis and column	320 mm
Distance between spindle nose and table	80-680 mm
Distance between spindle nose and base	1140 mm
Table dimensions	500 x 380 mm
Slot	14 mm
Tilting table	±90°
Vice	145 mm
Base dimensions	470 x 670 mm
Motor	400 V 50 Hz 1,1/1,5 kW
Cooling pump	400 V 50 Hz 75 W
Dimensions	500 x 750 x 2000 mm
Net weight	400 kg

Included

Drill chuck with key 1 - 16 mm B18
Spindle drilled MT 4 B18
Reduction sleeve MT 4/3
Reduction sleeve MT 3/2

Packaging dimensions	795x570x2100 h mm
Gross weight	427,50 kg
EAN Code	8012667243937