

CON SONDA PER MISURAZIONE TEMPERATURA, CONTINUITÀ SONORA E CONTROLLO DIODI.



€30,30
~~€40,90~~



DCV	200 mV $\pm 0,5\%$
DCV	2 V - 20 V - 200 V $\pm 0,8\%$
DCV	1000 V $\pm 0,1\%$
ACV	2mV - 20 V - 200 V $\pm 1,0\%$
ACV	750 V $\pm 1,2\%$
DCA	2 mA - 20 mA $\pm 1,8\%$
DCA	200 mA $\pm 2,0\%$
DCA	20 A $\pm 2,0\%$
ACA	200 mA $\pm 2,0\%$
ACA	20 A $\pm 3,0\%$
RES	200 Ω $\pm 1,0\%$
RES	2K Ω - 20K Ω - 200K Ω - 2M Ω $\pm 1,0\%$
RES	20 M Ω $\pm 1.0\%$
RES	200 M Ω $\pm 5.0\%$
CAP	2000 pF - 20 nF - 200 nF - 2 μ F - 20 μ F $\pm 4\%$
Temperatura	-40 °C - 400 °C $\pm 1,0\%$
Temperatura	400 °C - 1000 °C $\pm 1,5\%$
Batteria	1 x 9 V
Peso lordo	0,45 kg
Dimensioni imballo	190x65x140 h mm
Codice EAN	8012667164515



Scatola

**Accessori
Inclusi**

Batteria 9V